

Approved For Release 2008/07/02 : CIA-RDP80T00246A000700880001-7

	· -	F PAGE FOR SPECIAL CONTROLS, IF ANY	
*	INFORMATION REPORT	This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C	
EPAR	ED AND DISSEMINATED BY	Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized per	
	CENTRAL INTELLIGENCE AGENCY	son is prohibited by law.	
NTRY	Rungary		
JECT		DATE DISTRIBUTED 9 May 57	
	Soil Research/Location of Military Bargacks	NO. OF PAGES NO. OF ENCLS.	
SAF	review completed.	2	
		SUPPLEMENT TO REPORT #	
	THIS IS UNEVALUATED INFORM	MATION	
	This report is the result of a joint collection the Army and CIA and is disseminated in accordants.	n effort by the Air Force, nce with the provisions of NSCID	
_			
1.			
	The institute has five branches or departments (b) soil testing, (c) chemical (d) water resear	ch and (e) administration.	
2.	The institute has five branches or departments (b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 18 12 m, and dril depths of 25-30 m. A typical testing party con two helpers, one technician and one draftsman.	The tests consisted plastic limitations. In the drills of 55mm in diameter ls of 203 mm in diameter for	
2.	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 18 12 m, and dril depths of 25-30 m. A typical testing party con two helpers, one technician and one draftsman.	The tests consisted plastic limitations. In the drills of 55mm in diameter is of 203 mm in diameter for sisted of one drilling foreman, proportions in concrete was important branches of the soil ther things tests the water	
2.	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 18 12 m, and dril depths of 25-30 m. A typical testing party con two helpers, one technician and one draftsman. Cement usually 400 kg per cubic meter. Another of the institute was the chemical branch which among o samples for sulphate content in order to determ	The tests consisted plastic limitations. In the drills of 55mm in diameter ls of 203 mm in diameter for sisted of one drilling foreman, proportions in concrete was important branches of the soil ther things tests the water ine the corrosi a effects the	
2.	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 19 12 m, and dril depths of 25-30 m. A typical testing party con two helpers, one technician and one draftsman. Cement usually 400 kg per cubic meter. Another of the institute was the chemical branch which among o samples for sulphate content in order to determ water might have on the foundation.	The tests consisted plastic limitations. In the drills of 55mm in diameter ls of 203 mm in diameter for sisted of one drilling foremen, proportions in concrete was important branches of the soil ther things tests the water ine the corrosis a effects the	
2.	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 10 12 m, and dril depths of 25-30 m. A typical testing party con two helpers, one technician and one draftsman. Cement usually 400 kg per cubic meter. Another of the institute was the chemical branch which among or samples for sulphate content in order to determ water might have on the foundation. Soil conditions prevailing in the following are:	The tests consisted plastic limitations. In the drills of 55mm in diameter ls of 203 mm in diameter for sisted of one drilling foremen, proportions in concrete was important branches of the soil ther things tests the water ine the corrosis a effects the as are as follows: h soil) down to 50 meters.	
2.	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 10 12 m, and dril depths of 25-30 m. A typical testing party con two helpers, one technician and one draftsman. Cement usually 400 kg per cubic meter. Another of the institute was the chemical branch which among or samples for sulphate content in order to determ water might have on the foundation. Soil conditions prevailing in the following are: a. Stalinvaros [46 58N-18 55E] losss (yellowis)	The tests consisted plastic limitations. In the drills of 55mm in diameter is of 203 mm in diameter for sisted of one drilling foreman, proportions in concrete was important branches of the soil ther things tests the water ine the corrosis a effects the as are as follows: h soil) down to 50 meters.	
2.	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 18 12 m, and dril depths of 25-30 m. A typical testing party com two helpers, one technician and one draftsman. Cement usually 400 kg per cubic meter. Another of the institute was the chemical branch which among o samples for sulphate content in order to determ water might have on the foundation. Soil conditions prevailing in the following are a. Stalinvaros [46 58N-18 55E] loess (yellowis) b. Komlo [46 11N-18 15E] clay to a depth of 25	The tests consisted plastic limitations. In the drills of 55mm in diameter is of 203 mm in diameter for sisted of one drilling foreman, proportions in concrete was important branches of the soil ther things tests the water ine the corrosi a effects the as are as follows: h soil) down to 50 meters. meters.	
3.	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 19 12 m, and dril depths of 25-30 m. A typical testing party com two helpers, one technician and one draftsman. Cement usually 400 kg per cubic meter. Another of the institute was the chemical branch which among o samples for sulphate content in order to determ water might have on the foundation. Soil conditions prevailing in the following are a. Stalinvaros [46 58N-18 55E] loess (yellowis) b. Komlo [46 llN-18 15E] clay to a depth of 25 c. Györ [47 41N-17 38E] gravel to a depth of 25 d. Bukk mountains between Miskolc [48 06N- 20 2) limestone. Usually the construction sites for which I made proposed construction. I know of one border sta	The tests consisted plastic limitations. In the drills of 55mm in diameter ls of 203 mm in diameter for sisted of one drilling foreman, proportions in concrete was important branches of the soil ther things tests the water ine the corrosic a effects the as are as follows: h soil) down to 50 meters. meters. 20 meters. 47E7 and Eger 47 38N = 20 39E7 soil test borings were for ation which probably has been	
2°	(b) soil testing, (c) chemical (d) water resear of determination of water content, density and field we had hand operated boring machines with which were used for depths of 19 12 m, and dril depths of 25-30 m. A typical testing party com two helpers, one technician and one draftsman. Cement usually 400 kg per cubic meter. Another of the institute was the chemical branch which among o samples for sulphate content in order to determ water might have on the foundation. Soil conditions prevailing in the following are a. Stalinvaros [46 58N-18 55E] loess (yellowis) b. Komlo [46 llN-18 15E] clay to a depth of 25 c. Györ [47 41N-17 38E] gravel to a depth of 26 d. Bukk mountains between Miskolc [48 06N- 20 2) limestone. Usually the construction sites for which I made proposed construction. I know of one border sta	The tests consisted plastic limitations. In the drills of 55mm in diameter ls of 203 mm in diameter for sisted of one drilling foreman, proportions in concrete was important branches of the soil ther things tests the water ine the corrosic a effects the as are as follows: h soil) down to 50 meters. meters. 20 meters. 47E7 and Eger 47 38N = 20 39E7 soil test borings were for ation which probably has been	

C-O-N-F-I-D-R-N-TI-A-L

- 2 -

25X1


- a. Overlay of proposed border guard barracks
- b. Overlay of border guard barracks
- c. Overlay of "Blue" AVH Barracks.


-end-

C-O-N-F-I-D-E-N-T-I-A-L

Approved For Release 2008/07/02 : CIA-RDP80T00246A000700880001-7







Confidential

- J	-	CIA-RDP80T0024	0.000			
Action 1	•		15			25X1
		SHEET 5069				
		AMC CERIES A				
		(CONFIDENTI	* ()			
		•		,		
			•			
	·		•			
		• .	·			
					•	
		·		•		
	,					
v			·		•	
			•	•		
_	NOWLY CONE	T0 50				
. ? **	En Beick.	Ridge	•			
ε;	- MS BARRAS	KI FOR		- 19		
3.	2 AVO (AYH) 45%)	. (°)			•	
	, - ,	•	•			
		•				Q ³
		· .				
			*			<u> </u>
			-			
			-			
		•	•			
		•				
	•					·
	•		·			
•		•				
	•		•			
•		•	,			•
		-	ifidenti:	•	•	

Approved For Release 2008/07/02 : CIA-RDP80T00246A000700880001-7 tial

MIDDLE DANUBE (e)

Third ED ANS

25X1

PROPOSED SITE
FOR BOODER BUSING BERRARE (C)
1 STORY
DRICK BIDG

JUL 1955")

(CONFIDENTIAL)

24

Confidential

Approved For Release 2008/07/02 : CIA-RDP80T00246A000700880001-7-1al	
MIDTLE DANIBE	
1 :00,000	
Third ED AMS	
(CONFIDENTIAL)	25X1
34	•
83——	
•	
FIVE I STORY	
BARKE BARRABES	
FOR BORDER GUANDE (E)	
(Enconframe) " (Seesen Ava)	-
Geren Avol	
•	
ullet	
• • • • • • • • • • • • • • • • • • •	•
	69
•	
	4 1
\cdot	
•	,
	2
	2
Confidential	2
	2

